

## Specifications

<b>Dimensions</b>	45 ft. (13.72 m) long x 8 ft. 6 in. (2.59 m) wide x 11ft. (3.35 m) high, including towing assembly
<b>Weight</b>	28,000 lb. (12700.59 kg)
<b>Capacity</b>	21,000 gal. (79493.65 l) (nominal)
<b>Valves</b>	Two 4 in. (10.16 cm) butterfly valve drains with NPT threads, one at each end in recessed sumps One 4 in. (10.16 cm) valve mid-way on tank front
<b>Manways</b>	Two to three 21–25 in. (53.34– 63.50 cm) manways, typically at front, side and rear All manways equipped with butterfly-style nuts
<b>Inspection Hatch</b>	One 21 in. (53.34 cm) top inspection hatch with safety bars
<b>Fill/Overflow Line</b>	Top 3 in. (7.62 cm) feed line with cap and NPT threads
<b>Vent</b>	8 in. (20.32 cm) vent/hatch equipped with pressure relief valve 4 or 16 oz. (113.40 g or 453.59 g) psi for pressure, 0.4 oz. (11.34 g) psi for vacuum
<b>Other Connections</b>	Additional 4 in. (10.16 cm) and 2 in. (5.08 cm) NPT connections with caps

## Options & Accessories

- Secondary Containment Berm
- Steam Coils
- Epoxy or Non-Coated Interiors
- Camlock Fittings
- Vapor-Tight
- Suction and Discharge Hoses
- Level Gauges

Specifications are approximate and may vary. Ask your sales representative for specific dimensions for the unit we supply to you.

